



369.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel Elkhart Lake SoC !
- HB368F21 !

- Intel Elkhart Lake SoC Processor
- 1\* DDR4 3200MHz SO-DIMM up to 32GB
- 2\* USB3.1 (Gen.2), 4\* USB2.0, 2\* RJ45, 1\* Audio (MIC + Line-out), 1\* Line-IN, 3\* DP, 2\* COM, 1\* GPIO
- 160.2\*106\*27 mm
- DC12V\_40W Adapter
- Support TPM2.0 (option)

|                    |  |  |
|--------------------|--|--|
| Model              | - HB368F21-6210-S (non-WiFi)<br>- HB368F211-6210-S (WiFi)  |  |
| CPU/Chipset        | - Intel® Elkhart Lake SoC Processor(N6210, TDP 6.5W)   |  |
| BIOS               | - AMI Flash ROM  |  |
| Memory             | - 1* DDR4 3200MHz SO-DIMM up to 32GB   |  |
| Network            | - 2* Realtek RTL8119I GbE  |  |
| Graphics           | - Intel® HD Graphics, shared memory<br>- 3* DP (Max Resolution: 4096x2160@60Hz)<br>- Support Triple Displays |  |
| Storage            | - 1* M.2 M-key (2242/2280, PCIe Gen.3 x2/SATA interface) support NVME<br>- 32GB eMMC onboard (option)        |  |
| Expansion          | - 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface)<br>- 1* M.2 B-key (3042, USB3.0 interface)             |  |
| Rear Panel I/O     | - 2* RJ45<br>- 1* DC in (Lockable)   |  |
| Front Panel I/O    | - 1* Power button + Power LED<br>- 4* USB2.0<br>- 1* Audio(Line out+MIC)<br>- 1* Line in<br>- 3* DP          |  |
| Internal Connector | - SIM Card Holder  |  |

|              |  |
|--------------|--|
| Power Source | - Adapter : AC 90~240V input / DC12V_40W output<br>- MB : DC12~36V input   |
| Compliance   | - CE, FCC, LVD, RoHS, ErP Ready  |
| Dimensions   | - System: 160.2 (W) x 106 (D) x 27 (H) mm<br>- Net Weight: 0.61KG: Gross Weight: 1.12KG  |
| Temperature  | - Operating Temperature: -20 ~ 60° C (Under the condition of using M.2 interface SSD)<br>- Storage Temperature: -20 ~ 60° C<br>- Humidity: 10% ~ 90% RH @40°C (non-condensing) |
| OS Support   | - Windows 11, Linux  |