

9.95 EUR

incl. 19% VAT, plus [shipping](#)

- M.2 NGFF !
- UMTS / 3G !
- LTE (USA) !



Support: [Specifications](#) | [Drivers \(Windows\)](#) | [Dialer Software](#)

The ME906V is a NGFF modem module, supporting LTE (USA), Penta-band DC-HSPA+/HSPA+/HSPA/WCDMA, Dual-band CDMA/DO BC0/BC1, low power consumption, Global Navigation Satellite System (GNSS). In addition, the ME906V supports NGFF features to optimize performance, power consumption, and usability. ME906V is the ideal choice for Ultrabook, notebook, tablet etc.

Manufacturer	Huawei
Model	ME906V
Unlocked	Ready for use with global services. No contract required.
Network Bands	<ul style="list-style-type: none"> • LTE (FDD) B1/B2/B4/B5/B8/B13/B17 CDMA/EVDO BC0/BC1 Penta-band DC-HSPA+/HSPA+/HSPA/UMTS B1/B2/B4/B5/B8 Quad-band EDGE/GPRS/GSM 1900/1800/900/850 MHz
Data Speed	<p>1x: UL (153.6 kbps)/DL (153.6 kbps)</p> <p>EVDO Rev.A: UL (1.8 Mbps) /DL (3.1 Mbps)</p> <p>GPRS/EDGE: Multi-slot Class 12</p> <p>WCDMA PS: UL (384 kbps)/ DL (384 kbps)</p> <p>DC-HSPA+ :UL (5.76 Mbps)/ DL (42 Mbps)</p> <p>LTE FDD: UL (50 Mbps)/ DL (100 Mbps) @Bandwidth 20M (CAT3)</p>
Interface	<p>Antenna interfaces x 2</p> <p>M.2 Socket 2</p> <p>USB 2.0 interface high speed</p> <p>Power supply</p> <p>UICC interface</p>
Power Supply	<p>Supply voltage range: 3.135V~4.4V (3.3 V recommended)</p> <p>Normal operation: -10°C to +55°C</p>
Temp Range	<p>Extended operation: -20°C to +70°C</p> <p>Storage: -40°C to +85°C</p>
GPS	GNSS: GPS Standalone, A-GPS, GPS XTRA, Glonass
Dimensions	<ul style="list-style-type: none"> • 42x30x2.3 mm
Supported Systems	Windows 7/Windows 8/Android 4.0 or above

Special Features

SIM Hotswap
IPV6
BodySAR
Ultrabook feature support(ACT, WiFi Offload , DPTF)
Tunable Antenna
Supporting MO and MT
Supporting formats of PDU

Package Contents

Point-to-point and cell broadcast
New Huawei ME906V NGFF Embedded Module.